

A division of Safe Environments Pty Ltd www.SafeEnvironments.com.au

4/40 Bessemer Street Blacktown NSW 2148 Phone 02 9621 3706 ABN 80 118 534 768

23 October 2014

Test Report No. R7399f

Slip Resistance Classification of New Pedestrian Surface Materials

AS 4586:2013 Appendix A (Wet Pendulum Test)

The slip resistance Classification has been determined for unused surfaces using specific conditions. Factors such as usage, cleaning systems, applied coatings and patterns of wear may affect the characteristics of the surface.

Requested by:

Birrus Matting Systems

Client Address:

12 Overseas Drive

Product Manufacturer:

Noble Park North VIC 3174 Birrus Matting Systems

Product Description:

Duragrit Abrasive Grit Insert

Test conducted according to:

Location:

AS 4586:2013 Appendix A Level 7, 552 Lonsdale Street Melbourne VIC 3000

Conducted by:

Amy Morris

Date:

17 October 2014

Temperature:

20°C

Sample:

Unfixed

Cleaning:

None Grade P 400 paper dry followed

Rubber slider used:

Slider 96

Conditioned:

by wet lapping film

Slope of specimen: Direction of Test: Tested on a flat level surface

Parallel to inserts

	Specimen 1	Specimen 2	Specimen 3	Specimen 4	Specimen 5
Mean BPN of last 3 swings:	74	72	73	73	74

Reported SRV of Sample:	73
Class:	P5



Martin Daniel

Materials Scientist